

Pelican Case Specification Sheet

Model	INTERNAL DIMS (mm)			DEPTH (mm)		EXTERNAL DIMS (mm)			Wt w/o foam (kg)	Wt w/ foam (kg)	Buoyancy Max. (kg)	Volume Internal (Litres)	Temp. Range Min./Max. (°C)	Colours	Wheels	Ext. Handle	OPTIONAL ACCESSORIES							Certificates	Model
	L int. (mm)	W int. (mm)	D int. (mm)	BASE int. (mm)	LID int. (mm)	L ext. (mm)	W ext. (mm)	D ext. (mm)									Pick n Pluck foam set	Padded Divider	Panel Frame Kit	Lid	Organiser	Mobility Kit	Laptop Insert		
Memory Card Cases																									
915	122.0	57.0	14.0	7.0	7.0	141.0	83.0	22.0	0.1	0.1		0.1		B	-	-	-	-	-	-	-	-	-	915	
945	122.0	57.0	14.0	7.0	7.0	141.0	83.0	22.0	0.1	0.1		0.1		B	-	-	-	-	-	-	-	-	-	945	
Micro Cases																									
1010	111.0	73.0	43.0	24.0	18.0	138.0	103.0	54.0	0.18	0.19	0.2	0.3	-23 / 93	B, BI, Y, R, C*	-	-	1012	-	-	-	-	-	-	IP67	1010
i1010	111.0	73.0	43.0	24.0	18.0	138.0	103.0	54.0	0.18	0.19	0.2	0.3	-23 / 93	B, BI, Y, P, W, G, S	-	-	-	-	-	-	-	-	-	-	i1010
1015	131.0	67.0	35.0	24.0	11.0	170.0	99.0	47.0	n/a	0.21	0.5	0.3	n/a	B, Y	-	-	-	-	-	-	-	-	-	IP67	1015
i1015	131.0	67.0	35.0	24.0	11.0	170.0	99.0	47.0	n/a	0.21	0.5	0.3	n/a	B	-	-	-	-	-	-	-	-	-	-	i1015
1020	135.0	90.0	43.0	24.0	18.0	162.0	121.0	54.0	0.25	0.25	0.3	0.5	-23 / 93	B, BI, Y, R, C*	-	-	1022	-	-	-	-	-	-	IP67	1020
1030	162.0	67.0	52.0	32.0	18.0	191.0	98.0	62.0	0.27	0.28	0.5	0.6	-23 / 93	B, BI, Y, R, C*	-	-	1032	-	-	-	-	-	-	IP67	1030
1040	165.0	98.0	44.0	24.0	18.0	191.0	129.0	54.0	0.32	0.32	0.6	0.7	-23 / 93	B, BI, Y, R, C*	-	-	1042	-	-	-	-	-	-	IP67	1040
1050	160.0	93.0	70.0	49.0	18.0	191.0	129.0	79.0	0.37	0.38	0.8	1.0	-23 / 93	B, BI, Y, R, C*	-	-	1052	-	-	-	-	-	-	IP67	1050
1060	210.0	108.0	57.0	37.0	18.0	238.0	141.0	67.0	0.45	0.57	1.1	1.3	-23 / 93	B, BI, Y, R, C*	-	-	1062	-	-	-	-	-	-	IP67	1060
Small Cases																									
1120	184.0	121.0	78.0	65.0	13.0	206.0	167.0	90.0	0.53	0.56	2.3	1.7	-23 / 99	B,S,Y,O,BL,DT,OD	-	-	1121	-	1120PF	-	-	-	-	-	1120
1150	208.0	149.0	92.0	73.0	19.0	232.0	192.0	111.0	0.80	0.90	3.6	2.9	-23 / 99	B,S,Y,O,BL,DT,OD	-	-	1151	-	1150PF	-	-	-	-	-	1150
1170	268.0	153.0	80.0	53.0	27.0	296.0	212.0	96.0				3.3			-	-	1171	-	-	-	-	-	-	1170	
1200	235.0	181.0	105.0	74.0	30.0	270.0	246.0	124.0	1.20	1.30	5.5	4.5	-23 / 99	B,S,Y,O,DT,OD	-	-	1201	-	1200PF	-	-	-	-	-	1200
1300	251.0	178.0	155.0	125.0	30.0	270.0	246.0	175.0	1.40	1.60	5.6	6.9	-23 / 99	B,S,Y,O,DT,OD	-	-	1301	-	1300PF	-	-	-	-	-	1300
1400	300.0	225.0	132.0	102.0	30.0	340.0	295.0	152.0	1.80	2.00	9.1	8.9	-23 / 99	B,S,Y,O,DT,OD	-	-	1401	-	1400PF	-	-	-	-	-	1400
Laptop Cases																									
1430	344.0	146.0	297.0	246.0	51.0	430.0	244.0	341.0	2.54	2.95	26.8	14.9	-23 / 99	B,Y,O,DT,OD	-	-	1431	1435	1430PF	1439				+	1430
1440	434.0	191.0	406.0	355.0	51.0	500.0	305.0	457.0	6.58	7.48	68.0	33.7	-23 / 99	B,S,Y,O,DT,OD	Y	+	1441	445/4	-	1445/4	-	-	-	+	1440
1470	397.0	265.0	95.0	60.0	35.0	424.0	332.0	111.0	1.94	2.47	11.3	10.0	-23 / 99	B,DT	-	-	1471	-	1470PF	-	-	-	-	+	1470
1490	451.0	289.0	105.0	67.0	38.0	505.0	354.0	119.0	2.48	2.95	18.6	13.7	-23 / 99	B,DT	-	-	1491	-	1490PF	1498	-	-	-	+	1490
1495	479.0	333.0	97.0	68.0	28.0	549.0	438.0	124.0	3.28	3.80	20.5	15.5	-23 / 99	B,DT	-	-	-	-	-	1495AL	-	-	-	+	1495



Micro Cases : Polycarbonate Liner : Thermoplastic Rubber 1.5mm thick
Cases : Copolymer Polypropylene Latches : ABS Pins: Stainless Steel
 O'Ring : Neoprene Sponge Foam : Polyurethane Purge : GORTEX membrane



PROTECTIVE CASES
 U3 / 15 May Holman Drive Bassendean WA
 PH : +61 (0)8 6161 0295 EM : enquiry@protectivecases.com.au

Note : Dimensions derived from various sources E&OE.

Pelican Case Specification Sheet

Model	INTERNAL DIMS (mm)			DEPTH (mm)		EXTERNAL DIMS (mm)			Wt w/o foam (kg)	Wt w/ foam (kg)	Buoyancy Max. (kg)	Volume Internal (Litres)	Temp. Range Min./Max. (°C)	Colours	Wheels	Ext. Handle	OPTIONAL ACCESSORIES							Certificates	Model
	L int. (mm)	W int. (mm)	D int. (mm)	BASE int. (mm)	LID int. (mm)	L ext. (mm)	W ext. (mm)	D ext. (mm)									Pick n Pluck foam set	Padded Divider	Panel Frame Kit	Lid	Organiser	Mobility Kit	Laptop Insert		
Hardback Cases																									
1055	217.0	140.0	22.0	11.0	11.0	239.0	178.0	31.0	0.34	0.37	-	0.7	-23 / 49	B	-	-	-	-	-	-	1055CC	-	1055		
1065	253.0	197.0	21.0	10.0	10.0	276.0	236.0	31.0	0.33	0.57	-	1.0	-23 / 49	B	-	-	-	-	-	-	1065CC	-	1065		
1070	325.0	227.0	18.0	9.0	9.0	388.0	304.0	41.0	1.05	1.27	-	1.3	-23 / 49	B	-	-	-	-	-	-	-	-	-		
1075	282.0	201.0	41.0	21.0	21.0	314.0	248.0	54.0	0.64	0.70	-	2.3	-23 / 49	B	-	-	-	-	-	-	1075CC	-	1075		
1085	363.0	263.0	50.0	25.0	25.0	397.0	315.0	63.0	1.18	-	-	4.8	-23 / 49	B	-	-	-	-	-	-	1085CC	-	1085		
1095	401.0	283.0	52.0	26.0	26.0	436.0	336.0	66.0	1.32	-	-	5.9	-23 / 49	B	-	-	-	-	-	-	1095CC	-	1095		
Medium Cases																									
1440	434.0	190.0	406.0	355.0	51.0	500.0	305.0	457.0	6.58	7.48	68.0	33.5	-40 / 99	B,S,O,Y,DT,OD*	Y	Y	-	1444	-	1447	-	-	-	-	
1450	371.0	258.0	152.0	108.0	44.0	406.0	330.0	174.0	2.50	2.90	13.6	14.5	-23 / 99	B,S,Y,O,DT,OD	-	-	1451	1455	1450PF	-	-	-	-	+	1450
1460	471.0	252.0	277.0	153.0	125.0	529.0	323.0	321.0	3.97	5.66	37.2	32.9	-40 / 99	B, DT, OD*	-	+	1461	-	-	-	-	-	-	-	1460
1500	425.0	284.0	155.0	106.0	46.0	470.0	357.0	176.0	2.90	3.20	22.7	18.7	-23 / 99	B,S,Y,O,DT,OD	-	-	1501	1505	1500PF	1508/09	-	-	-	+	1500
1510	501.0	279.0	193.0	148.0	45.0	559.0	351.0	229.0	5.44	6.17	29.1	27.0	-23 / 99	B,DT,OD	Y	+	1511	1515	-	1519	-	-	-	+	1510
1520	454.0	324.0	171.0	125.0	46.0	485.0	392.0	192.0	3.76	4.24	18.1	25.2	-23 / 99	B,S,Y,O,DT,OD	-	-	1521	1525	1520PF	1508/09	-	-	-	+	1520
1550	468.0	355.0	193.0	149.0	44.0	524.0	428.0	206.0	4.80	5.40	31.7	32.1	-23 / 99	B,S,Y,O,DT,OD	-	-	1551	1555	1550PF	-	-	-	-	+	1550
Large Cases																									
1560	517.0	392.0	229.0	178.0	51.0	560.0	455.0	265.0	7.71	9.07	47.2	46.4	-23 / 99	B,S,Y,O,DT,OD	Y	+	1562	1565	-	1569	-	-	-	+	1560
1600	544.0	419.0	200.0	155.0	44.0	616.0	493.0	220.0	5.90	6.40	34.0	45.6	-23 / 99	B,S,Y,O,DT,OD	-	-	1601	1605	-	1609	-	-	-	+	1600
1610	553.0	424.0	270.0	218.0	52.0	630.0	500.0	302.0	9.07	10.20	54.4	63.3	-23 / 99	B,DT,OD	Y	+	1611	1615	-	1609	-	-	-	+	1610
1620	545.0	417.0	318.0	266.0	52.0	626.0	492.0	350.0	11.10	11.80	68.0	72.3	-23 / 99	B,DT,OD	Y	+	1621	1625	-	1609	-	-	-	+	1620
1630	703.0	533.0	394.0	308.0	83.0	794.0	615.0	444.0	14.06	16.33	158.8	147.6	-23 / 99	B,DT,OD	Y	+	1631	1635	-	-	-	-	-	+	1630
1640	602.0	609.0	353.0	302.0	51.0	691.0	698.0	414.0	15.42	17.24	165.6	129.4	-23 / 99	B,DT,OD	Y	+	1641	1645	-	1649	-	-	-	+	1640
1650	725.0	445.0	270.0	219.0	51.0	802.0	520.0	361.0	13.20	16.10	82.1	87.1	-23 / 99	B,DT,OD	Y	+	1651	1655	-	1659	-	-	-	+	1650
1660	716.0	499.0	448.0	359.0	89.0	802.0	584.0	495.0	15.50	19.10	158.8	160.1	-23 / 99	B,DT,OD	Y	+	1661	1665	-	1669	-	-	-	+	1660
1670	713.0	419.0	233.0	188.0	46.0	788.0	492.0	284.0	10.43	11.79	82.6	69.6	-23 / 99	B	Y	+	1671	-	-	-	-	-	-	+	1670
1690	762.0	635.0	381.0	308.0	73.0	849.0	721.0	448.0	15.42	19.50	186.0	184.4	-23 / 99	B,DT,OD	Y	+	+	-	-	-	-	-	-	+	1690



PELICAN

Micro Cases : Polycarbonate Liner : Thermoplastic Rubber 1.5mm thick

Cases : Copolymer Polypropylene Latches : ABS Pins: Stainless Steel

O'Ring : Neoprene Sponge Foam : Polyurethane Purge : GORTEX membrane



PROTECTIVECASES

PROTECTIVE CASES

U3 / 15 May Holman Drive Bassendean WA

PH: +61 (0)8 6161 0295 EM : enquiry@protectivecases.com.au

Note : Dimensions derived from various sources E&OE.

Pelican Case Specification Sheet

Model	INTERNAL DIMS (mm)			DEPTH (mm)		EXTERNAL DIMS (mm)			Wt w/o foam (kg)	Wt w/ foam (kg)	Buoyancy Max. (kg)	Volume Internal (Litres)	Temp. Range Min./Max. (°C)	Colours	Wheels	Ext. Handle	OPTIONAL ACCESSORIES							Certificates	Model
	L int. (mm)	W int. (mm)	D int. (mm)	BASE int. (mm)	LID int. (mm)	L ext. (mm)	W ext. (mm)	D ext. (mm)									Pick n Pluck foam set	Padded Divider	Panel Frame Kit	Lid	Organiser	Mobility Kit	Laptop Insert		
Large/Cube Cases																									
0340	457.0	457.0	457.0	318.0	102.0	521.0	521.0	489.0	10.89	13.50	100.0	95.4	-23 / 99	B,DT,OD	-	+	341	345	-	0349			+	0340	
0350	508.0	508.0	508.0	381.0	127.0	572.0	570.0	540.0	11.79	14.52	122.0	131.1	-23 / 99	B,DT	-	-	351	355	-	0359		0357	+	0350	
0370	610.0	610.0	610.0	457.0	114.0	673.0	673.0	641.0	14.50	18.60	211.0	227.0	-23 / 99	B,DT,OD	-	-	371	375	-	0379		0357	+	0370	
0500	887.0	468.0	641.0	584.0	57.0	1014.0	595.0	727.0	22.68	26.58	353.8	266.8	-40 / 99	B	-	-								0500	
0550	1208.0	611.0	449.0	368.0	81.0	1296.0	699.0	579.0	35.92	43.09	372.0	331.7	-23 / 99	B	-	-								0550	
Long Cases																									
1700	908.0	343.0	133.0	44.0	89.0	968.0	406.0	155.0	7.30	7.70	62.1	41.4	-23 / 99	B,DT,OD	Y	-	1701	-	-	-			+	1700	
1720	1067.0	343.0	133.0	44.0	89.0	1127.0	406.0	155.0	7.60	8.60	73.0	48.7	-23 / 99	B,DT,OD	Y	-	1721	-	-	-			+	1720	
1730	863.0	609.0	317.0	63.0	254.0	952.0	689.0	365.0	17.24	13.61	188.7	166.6	-40 / 99	B,DT,OD	Y	-	1731	-	-	-			+	1730	
1740	1040.0	328.0	308.0	65.0	243.0	1121.0	409.0	355.0	9.98	12.25	121.1	105.1	-40 / 99	B,DT,OD	Y	-	1741	-	-	-			+	1740	
1750	1283.0	343.0	133.0	44.0	89.0	1346.0	406.0	155.0	10.66	11.60	85.0	58.5	-23 / 99	B,DT,OD	Y	-	1751	-	-	-			+	1750	
1770	1386.0	396.0	219.0	48.0	171.0	1386.0	396.0	219.0	13.15	16.33	127.0	120.2		B,DT,OD	Y	-	1771	-	-	-			+	1770	
1780	1066.0	559.0	383.0	192.0	185.0	1140.0	643.0	419.0	17.42	22.23	226.8	228.2	-40 / 99	B,DT,OD	Y	-	1781	-	-	-			+	1780	

COLOURS CODES ARE :

MICRO CASES

B = BLACK

BI = BLUE

Y = YELLOW

R = RUBY

C* = CLEAR

CASES

B = BLACK

BI = BLUE

O = ORANGE

S = Silver/GREY

Y = YELLOW

DT = DESERT TAN

OD = OUTDOOR GREEN (BY SPECIAL ORDER)



PELICAN

Micro Cases : Polycarbonate Liner : Thermoplastic Rubber 1.5mm thick

Cases : Copolymer Polypropylene Latches : ABS Pins: Stainless Steel

O'Ring : Neoprene Sponge Foam : Polyurethane Purge : GORTEX membrane



PROTECTIVECASES

PROTECTIVE CASES

U3 / 15 May Holman Drive Bassendean WA

PH : +61 (0)8 6161 0295 EM : enquiry@protectivecases.com.au

Note : Dimensions derived from various sources E&OE.

Pelican Case Specification Sheet

Model	INTERNAL DIMS (mm)			DEPTH (mm)		EXTERNAL DIMS (mm)			Wt w/o foam (kg)	Wt w/ foam (kg)	Buoyancy Max. (kg)	Volume Internal (Litres)	Temp. Range Min./Max. (°C)	Colours	Wheels	Ext. Handle	OPTIONAL ACCESSORIES							Certificates	Model
	L int. (mm)	W int. (mm)	D int. (mm)	BASE int. (mm)	LID int. (mm)	L ext. (mm)	W ext. (mm)	D ext. (mm)									Pick n Pluck foam set	Padded Divider	Panel Frame Kit	Lid	Organiser	Mobility Kit	Laptop Insert		
Elite Coolers																									
35QT	400.0	305.0	292.0			671.0	508.0	476.0	14.50			33.1		W,DT	-									35QT	
45QT	482.0	305.0	305.0			753.0	508.0	489.0	16.33			42.6		W,DT	-									45QT	
65QT	673.0	305.0	317.0			943.0	508.0	501.0	21.82			61.5		W,DT	-									65QT	
95QT	694.0	305.0	447.0			958.0	508.0	632.0	23.18			89.9		W,DT	-									95QT	
150QT	863.0	432.0	400.0			1140.0	635.0	619.0	29.94			142.0		W,DT	-									150Q	
250QT	1276.0	432.0	444.0			1552.0	698.0	698.0	41.73			236.6		W,DT	-									250Q	
Backpacks																									
U100	394.0	267.0	38.0			495.0	345.0	305.0	3.65			16.0		B	-									U100	
U140	267.0	190.0	38.0			495.0	345.0	292.0	3.10			18.0		B	-									U140	
U160	227.0	184.0	185.0			943.0	508.0	501.0	3.23			N/A		B	-									U160	
S100	385.0	264.0	25.0			470.0	330.0	254.0	3.24			25.0		B,G,O	-									S100	
S115	385.0	264.0	25.0			470.0	330.0	254.0	N/A			N/A		B	-									S115	
S130	385.0	264.0	25.0			470.0	330.0	254.0	3.24			25.0		B	-									S130	
S140	267.0	190.0	38.0			508.0	330.0	254.0	3.06			20.5		B,G,O	-									S140	
Phone Cases																									
CE1150	iPhone 5 & 5S Protector					133.0	69.0	13.0	0.04															CE1150	
CE1250	Samsung S4 Protector					146.0	79.0	13.0	0.05															CE1250	
CE1280	Samsung S4 Protector					262.0	215.0	19.0	0.05															CE1280	
CE2180	iPad Air					146.0	79.0	13.0	0.46															CE2180	
CE3180	iPad mini					219.0	171.0	20.0	0.34															CE3180	



Micro Cases : Polycarbonate Liner : Thermoplastic Rubber 1.5mm thick
Cases : Copolymer Polypropylene Latches : ABS Pins: Stainless Steel
 O'Ring : Neoprene Sponge Foam : Polyurethane Purge : GORTEX membrane



PROTECTIVE CASES
 U3 / 15 May Holman Drive Bassendean WA
 PH : +61 (0)8 6161 0295 EM : enquiry@protectivecases.com.au

Note : Dimensions derived from various sources E&OE.