

**Pelican Storm Case Specification Sheet**

Model	INTERNAL DIMS (mm)			DEPTH (mm)		EXTERNAL DIMS (mm)			Wt w/o foam (kg)	Wt w/ foam (kg)	Buoyancy Max. (kg)	Volume Internal (Litres)	Temp. Range Min./Max. (°C)	Colours	Wheels	Ext. Handle	OPTIONAL ACCESSORIES							Certificates	Model	
	L int. (mm)	W int. (mm)	D int. (mm)	BASE int. (mm)	LID int. (mm)	L ext. (mm)	W ext. (mm)	D ext. (mm)									Pick n Pluck foam set	Padded	Divider	Panel Frame Kit	Lid	Organiser	Mobility Kit			Laptop Insert
<b>Small Cases</b>																										
iM2050	241.0	190.0	108.0	70.0	38.0	300.0	249.0	119.0	1.36	1.22	7.57	5	-29 / 60	B, Y, OD			S	O	O							iM2050
iM2075	241.0	190.0	184.0	146.0	38.0	300.0	249.0	196.0	1.68	1.5	12.9	8	-29 / 60	B, Y, OD			S	O	O							iM2075
iM2100	241.0	234.0	152.0	102.0	51.0	361.0	289.0	165.0	2.22	1.91	15.34	9	-29 / 60	B, Y, OD			S	O	O							iM2100
<b>Laptop Cases</b>																										
iM2370	462.0	307.0	132.0	89.0	43.0	508.0	373.0	147.0	3.27	2.59	25.68	19	-29 / 60	B, OD			S	O	O							iM2370
<b>Medium Cases</b>																										
iM2200	432.0	160.0	157.0	102.0	51.0	411.0	322.0	170.0	2.77	2.22	20.03	11	-29 / 60	B, Y, OD	Y	Y	S	O	O							iM2200
iM2306	432.0	160.0	157.0	107.0	51.0	462.0	213.0	170.0	2.13	1.95	14.84	11	-29 / 60	B, OD			S	O	O							iM2306
iM2300	432.0	297.0	157.0	107.0	51.0	462.0	340.0	170.0	3.22	2.68	24.15	20	-29 / 60	B, Y, OD			S	O	O							iM2300
iM2400	457.0	330.0	170.0	119.0	51.0	487.0	386.0	185.0	3.54	2.95	31.96	26	-29 / 60	B, Y, OD			S	O	O							iM2400
iM2435	444.0	165.0	394.0			473.0	235.0	419.0		4.5		29	-29 / 60	B, OD			S	O								iM2435
iM2450	457.0	330.0	213.0	178.0	51.0	487.0	386.0	229.0	4.04	3.36	28.86	32	-29 / 60	B, OD			S	O	O							iM2450
iM2600	508.0	355.0	196.0	145.0	51.0	538.0	406.0	211.0	5.26	3.86	42.28	35	-29 / 60	B, Y, OD			S	O	O							iM2600
iM2620	508.0	355.0	254.0	203.0	51.0	538.0	406.0	269.0	6.58	5.67	58.93	46	-29 / 60	B, OD	Y	Y	S	O	O							iM2620
<b>Large Cases</b>																										
iM2500	520.0	292.0	183.0	132.0	51.0	551.0	358.0	226.0	6.21	5.03	39.64	28	-29 / 60	B, Y, OD	Y	Y	S	O	O							iM2500
iM2720	559.0	432.0	254.0	203.0	51.0	625.0	500.0	297.0	9.98	7.62	85.3	61	-29 / 60	B, Y, OD	Y	Y	S	O	O							iM2720
iM2750	559.0	432.0	322.0	272.0	51.0	625.0	500.0	366.0	10.61	8.39	105.97	78	-29 / 60	B, Y, OD	Y	Y	S	O	O							iM2750
iM2700	559.0	432.0	203.0	152.0	51.0	625.0	500.0	218.0	6.53	5.03	63.27	49	-29 / 60	B, Y, OD			S	O	O							iM2700
iM2875	571.0	536.0	289.0	239.0	51.0	632.0	602.0	333.0	11.16	9.12	117.58	88	-29 / 60	B, OD	Y	Y	S	O	O							iM2875
iM2950	736.0	457.0	267.0	216.0	51.0	795.0	518.0	310.0	13.02	9.43	118.23	90	-29 / 60	B, Y, OD	Y	Y	S	O	O							iM2950
iM2975	736.0	457.0	350.0	300.0	51.0	795.0	518.0	394.0	13.38	10.34	150.94	118	-29 / 60	B, OD	Y	Y	S	O	O							iM2975
iM3075	757.0	528.0	452.0	349.0	102.0	845.0	620.0	490.0	20.41	14.29	240.81	181	-29 / 60	B, OD	Y	Y	S	O	O							iM3075



**PELICAN STORM CASE™** Cases : Copolymer Polypropylene Latches : ABS Pins: Stainless Steel  
 O'Ring : Neoprene Sponge Foam : Polyurethane Purge : GORTEX membrane



**PROTECTIVE CASES**  
 U3 / 15 May Holman Drive Bassendean WA  
 PH : +61 (0)8 6161 0295 EM : enquiry@protectivecases.com.au

Note : Dimensions derived from various sources E&OE.

## Pelican Storm Case Specification Sheet

Model	INTERNAL DIMS (mm)			DEPTH (mm)		EXTERNAL DIMS (mm)			Wt w/o foam (kg)	Wt w/ foam (kg)	Buoyancy Max. (kg)	Volume Internal (Litres)	Temp. Range Min./Max. (°C)	Colours	Wheels	Ext. Handle	OPTIONAL ACCESSORIES								Certificates	Model
	L int. (mm)	W int. (mm)	D int. (mm)	BASE int. (mm)	LID int. (mm)	L ext. (mm)	W ext. (mm)	D ext. (mm)									Pick n Pluck foam set	Padded	Divider	Panel Frame Kit	Lid	Organiser	Mobility Kit	Laptop Insert		
<b>Long Cases</b>																										
iM3100	927.0	355.0	152.0	102.0	51.0	1011.0	419.0	170.0	8.98	6.89	64.67	50	-29 / 60	B, OD	Y									iM3100		
iM3200	1117.0	355.0	152.0	102.0	51.0	1198.0	419.0	170.0	9.57	8.03	77.48	60	-29 / 60	B, OD	Y									iM3200		
iM3220	1117.0	355.0	216.0	165.0	51.0	1198.0	419.0	234.0	11.25	9.25	108.17	86	-29 / 60	B, OD	Y									iM3220		
iM3300	1282.0	355.0	152.0	102.0	51.0	1366.0	419.0	170.0	10.43	8.66	88.85	69	-29 / 60	B, OD	Y									iM3300		



**PELICAN**<sup>™</sup>  
**STORM CASE**<sup>™</sup>

**Cases** : Copolymer Polypropylene   Latches : ABS   Pins: Stainless Steel  
O'Ring : Neoprene Sponge   Foam : Polyurethane   Purge : GORTEX membrane



**PROTECTIVE CASES**

U3 / 15 May Holman Drive Bassendean WA  
PH : +61 (0)8 6161 0295   EM : enquiry@protectivecases.com.au

**Note** : Dimensions derived from various sources   E&OE.