

## Pelican™ Light Specification Sheet

Model	Product Name	Length (mm)	Wt. (grams) w/batteries	Light Source	Batteries	Battery Included	Light Output (LUMENS)	Runtime	Beam Distance	Peak Beam Intensity (cd)	IP Rating	IS Certificate	Colours	Options	Model
<b>Personal Lights SMALL</b>															
1830	L4™ 1830 LED	157	30	LED	3x AAAA Alkaline	✓	5	32	13	44	IPX4	-	B, Y		1830
1900	MityLite™ 1900	104	50	Xenon	2x AAA Alkaline	✓	11	2	45	517	IPX7	CI D1	B, Y, O, BI, W, G		1900
1910	1910 LED	91	40	LED	1x AAA Alkaline	✓	39	1	62	967	IPX4	-	B		1910
1920	1920 LED	135	60	LED	2x AAA Alkaline	✓	67	3	81	1648	IPX4	-	B		1920
1930	L1™ 1930 LED	67	30	LED	4x LR 44 Alkaline	✓	12	4	17	70	IPX4	CI D1	B, Y		1930
1960	MityLite 1960 LED	139	50	LED	2x AAA Alkaline	✓	24	3	51	657	IPX7	-	B, Y		1960
1965	MityLite 1965 LED	139	50	LED	2x AAA Alkaline	✓	21	4	51	756	IPX4	CI II III D1	B, Y		1965
2140	Tracker 2140	89	50	Xenon	2x AAA Alkaline	✓	13	2	84	1761	IPX7	CI D2	Y		2140
2220	VB3™ 2220 LED	89	30	LED	2x CR2032	✓	9	34	12	38	IPX4	CI D1	B, O, Y, BI, R		2220
2300	MityLite™ 2300	143	100	Xenon	2x AA Alkaline	✓	11	5	43	478	IPX4	CI D1	B, Y		2300
2340	MityLite™ 2340	159	100	Xenon	2x AA Alkaline	✓*	10	5	43	461	IPX4	CI D1	B, Y		2340
<b>Personal Lights MEDIUM</b>															
1800	PeliLite™ 1800	152	220	Xenon	2x C Alkaline	×	21	7	131	4370	IPX7	CI II D2	B, Y, O		1800
1820	Pocket Sabre™ 1820	148	240	Xenon	2x C Alkaline	✓*	22	7	146	5466	IPX7	CI II III D2	B, Y, O		1820
2000	SabreLite™ 2000	198	360	Xenon	3x C Alkaline	×	53	5	158	6234	IPX7	CI D2	B, Y, O		2000
2010	SabreLite™ 2010 LED	206	380	LED	3x C Alkaline	×	109	32	144	5189	IPX7	CI II III D1	B, Y	PL Shroud	2010
2020	SabreLite™ 2020 Recoil™ LED	222	420	Recoil™ LED	3x C Alkaline	×	75	7	113	3211	IPX4	CI II D1	B, Y		2020
2400	StealthLite™ 2400	165	200	Xenon	4x AA Alkaline	✓	45.0	4	125	3934	IPX7	CI D1	B, Y, O, G		2400
2410	StealthLite™ 2410 LED	178	210	LED	4x AA Alkaline	✓	126	8	161	6500	IPX7	CI II III D1	B, Y	PL Shroud	2410
2430	MityLite™ 2430	165	170	Xenon	4x AA Alkaline	✓	70	2	104	2766	IPX4	CI D2	B, Y		2430
2450	StealthLite™ Rechargeable 2450	165	220	Xenon	4x AA NiMH	✓	35	4	122	3735	IPX7	CI II D2	B, Y		2450
2460	StealthLite™ Rechargeable 2460	178	220	LED	4x AA NiMH	✓	112	5	153	5828	IPX7	CI II D2	B, Y		2460
3310ELS	Emergency Lighting Station 3310	156	180	LED	3x AA Alkaline	✓	234 (H) 28 (L)	8.45 (H) 190 (L)	240 (H) 81 (L)	14500 (H) 1649 (L)	IPX7	-	photoluminescent		3310ELS
3310PL	LED Photoluminescent Flashlight	156	180	LED	3x AA Alkaline	✓	234 (H) 28 (L)	-8.45 (H) 190 (L)	240 (H) 81 (L)	14500 (H) 1649 (L)	IPX7	-	photoluminescent		3310PL
3315	3315 LED	156	180	LED	3x AA Alkaline	✓	113	10	153	5913	IPX4	CI II III D1	B, Y		3315

\* Batteries included in select packaging

IPX4 = Water Resistant

IPX7 = Water Proof (submerged to 1 meter for 30 min.)

IPX8 = Submersible (submerged to 100 meters for 4 hours)



**PROTECTIVE CASES**

U3 / 15 May Holman Drive Bassendean WA

PH : +61 (0)8 6161 0295

EM : enquiry@protectivecases.com.au

**Note : Dimensions derived from various sources E&OE.**

## Pelican™ Light Specification Sheet

Model	Product Name	Length (mm)	Wt. (grams) w/batteries	Light Source	Batteries	Battery Included	Light Output (LUMENS)	Runtime	Beam Distance	Peak Beam Intensity (cd)	IP Rating	IS Certificate	Colours	Options	Model
<b>Personal Lights LARGE</b>															
4000	KingLite™ 4000	238	2100	Xenon	8x D Alkaline	×	249	11	106	3168	IPX7	CI II D2	B, Y, O		4000
8040	M10 8040	286	520	Xenon	4x C Alkaline	×	67	5	198	9820	IPX4	CI II III D2	B, Y		8040
8050	M11 Rechargeable 8050	286	510	Xenon	4x C NiCad	✓	137	2	234	13707	IPX4	-	B, Y		8050
8060	LED Flashlight	322	660	LED	4x C NiMH (Rechargeable)	✓	179	7	279	19525	IPX4	-	B		8060
9410	9410 LED Lantern	222	1400	LED	4x D Ni-MH	✓	710 (H) 300 (L)	1.75 (H) 4.75 (L)	425 (H) 249 (L)	45,260 (H) 15,516 (L)	IPX4	-	B, Y		9410
9415	9415 LED Lantern (Boxed)	222	1400	LED	4x D Ni-MH	✓	413 (H) 159 (L)	4.30 (H) 12 (L)	325 (H) 201 (L)	26352 (H) 10076 (L)	IPX4	C1 D1	Y		9415
<b>Headlights</b>															
2600	HeadsUp Lite™ 2600	97	270	Krypton	4x AA Alkaline	✓	18	4	27	203	IPX7	CI II III D2	B		2600
2610	HeadsUp Lite™ 2610 LED	38	90	LED	3x AAA Alkaline	✓	30	19	28	194	IPX4	CI D1	B		2610
2620	HeadsUp Lite™ 2620	55	140	Xenon (H) LED (L)	3x AAA Alkaline	✓	26 (H) 14 (L)	2.25 (H) 18 (L)	44 (H) 29 (L)	491 (H) 216 (L)	IPX4	CI D1	B		2620
2640	HeadsUp Lite™ 2640	67	310	Halogen (H) LED (L)	4x AA Alkaline	✓	29 (H) 16 (L)	2.75 (H) 17 (L)	46 (H) 20 (L)	586 (H) 103 (L)	IPX4	CI D2	B		2640
2670	HeadsUp Lite 2670	63	140	LED	3x AAA Alkaline	✓	25	11	63	1001	IPX4		B		2670
2680	HeadsUp Lite™ 2680 Recoil™ LED	118	270	Recoil™ LED	4x AA Alkaline	✓	69	10	123	3788	IPX7	CI II III D2	B		2680
	HeadsUp Lite™ 2690 LED	71	120	LED	3x AAA Alkaline	✓	60	11	81	1664	IPX4	CI II III D2	B		2690
2720	2720 LED Headlight	-	110	LED	3x AAA Alkaline	✓	80 (H) 5 (L)	8 (H) 175 (L)	56 (H) 15 (L)	790 (H) 60 (L)	IPX4	-	B		2720
2740	2740 LED Headlight	57	90	LED	3x AAA Alkaline	✓	35 (H) 13 (L)	20 (H) 51 (L)	21 (H) 19 (L)	259 (H) 89 (L)	IPX4	-	B, W, BI		2740
2745	2745 LED Headlight	57	90	LED	3x AAA Alkaline	✓	33 (H) 17 (L)	20 (H) 40 (L)	35(H) 25(L)	309 (H) 165 (L)	IPX4	C1 D1	B, Y		2745
2750	2750 LED Headlight	57	100	LED	3x AAA Alkaline	✓	100 (H) 40 (L)	3.75 (H) 12 (L)	71 (H) 49 (L)	1250 (H) 591 (L)	IPX4	-	B, Y, W		2750
2755	2750 LED Headlight	57	100	LED	3x AAA Alkaline	✓	72 (H) 34 (L)	6 (H) 15 (L)	57 (H) 40 (L)	807 (H) 404 (L)	IPX4	C1 D1	B, Y		2755
2760	2760 LED Headlight	57	100	LED	3x AAA Alkaline	✓	133 (H) 90 (L)	2.25 (H) 3.5 (L)	117 (H) 86 (L)	3415 (H) 1841 (L)	IPX4	-	B, W, R		2760



IPX4 = Water Resistant  
 IPX7 = Water Proof (submerged to 1 meter for 30 min.)  
 IPX8 = Submersible (submerged to 100 meters for 4 hours)



**PROTECTIVE CASES**  
 U3 / 15 May Holman Drive Bassendean WA  
 PH : +61 (0)8 6161 0295  
 EM : enquiry@protectivecases.com.au

Note : Dimensions derived from various sources E&OE.

## Pelican™ Light Specification Sheet

Model	Product Name	Length (mm)	Wt. (grams) w/batteries	Light Source	Batteries	Battery Included	Light Output (LUMENS)	Runtime	Beam Distance	Peak Beam Intensity (cd)	IP Rating	IS Certificate	Colours	Options	Model
<b>Right Angled Lights</b>															
2250	VersaBrite™ 2250 Deluxe Light	98	90		2x AA Alkaline	✓	7	6	54	726	IPX4	CI II D2	B		2250
3610	Little Ed™ 3610 LED	191	300	LED	4x AA Alkaline	✓	72	7	102	2622	IPX7	CI II III D1	B, Y		3610
3660	Little Ed™ Rechargeable 3660 LED	191	300		4x AA NiMH (Rechargeable)	✓	73	4	99	2454	IPX4	CI II D2	B, Y		3660
3700	Big Ed™ 3700	178	580		4x C Alkaline		39 (H) 25 (L)	6.25 (H) 8.5 (L)	98 (H) 51 (L)	2437 (H) 684 (L)	IPX4	CI D2	Y	PL Shroud	3700
3715	3715 LED	136	410	LED	4x AA Alkaline		174 (H) 95 (L)	4.75 (H) 8.5 (L)	278 (H) 175 (L)	19,389 (H) 8,051 (L)	IPX4	CI D1	B, Y		3715
3750	Big Ed™ Rechargeable 3750	178	580		4x C NiCAD (Rechargeable)	✓	96 (H) 28 (L)	1.75 (H) 4 (L)	133 (H) 65 (L)	4,468 (H) 1,048 (L)	IPX4	CI D2	Y		3750
3765	3765 LED Rechargeable	136	410		4x AA Ni-MH (Rechargeable)	✓	172 (H) 94 (L)	3.25 (H) 5.25 (L)	274 (H) 181 (L)	18,784 (H) 8,232 (L)	IPX4	CI D2	B, Y		3765
<b>Dive Torches</b>															
1900N	Nemo™ 1900	104	50	Xenon	2x AAA Alkaline	✓	11	2	45	571	IPX8	-	B, Y, BI		1900
1960N	Nemo™ 1960	139	50	LED	2x AAA Alkaline	✓	24	3	51	657	IPX8	-	B, Y, BI		1960
2000N	Nemo™ 2000	198	360	Xenon	3x C Alkaline	×	53	5	158	6234	IPX8	-	B, Y, BI		2000
2010N	Nemo™ 2010 LED	2036	380	LED	3x C Alkaline	×	109	32	144	5189	IPX8	-	B, Y, BI		2010
2400N	Nemo™ 2400	165	200	Xenon	4x AA Alkaline	✓	45	4	125	3934	IPX8	-	B, Y, BI		2400
2410N	Nemo™ 2410 LED	178	210	LED	4x AA Alkaline	✓	126	8	161	6500	IPX8	-	B, Y, BI		2410
4300N	Nemo™ 4300	190	1040	Xenon	8x C Alkaline	×	276	6	143	5222	IPX8	-	B, Y, BI		4300
<b>Specialty Lights</b>															
2130	Mini Flasher™ 2130 LED	44	10	LED	2x L1154 Alkaline	✓	5	130	-	-	IPX7	-	Y		2130
2130IR	Mini Flasher™ 2130IR LED	44	10	LED	2x L1154 Alkaline	✓	-	65	-	-	IPX7	-	B		2130IR
2365	2365 LED	557	260	LED	2x AA Alkaline		49	7	81	1644	IPX4	-	B		2365
2490	StealthLite™ 2490 LED	317	230	LED	4x AA Alkaline		51	15	88	1930	IPX7	-	S		2490



IPX4 = Water Resistant  
 IPX7 = Water Proof (submerged to 1 meter for 30 min.)  
 IPX8 = Submersible (submerged to 100 meters for 4 hours)



**PROTECTIVE CASES**  
 U3 / 15 May Holman Drive Bassendean WA  
 PH : +61 (0)8 6161 0295  
 EM : enquiry@protectivecases.com.au

Note : Dimensions derived from various sources E&OE.

## Pelican™ Light Specification Sheet

Model	Product Name	Length (mm)	Wt. (grams) w/batteries	Light Source	Batteries	Battery Included	Light Output (LUMENS)	Runtime	Beam Distance	Peak Beam Intensity (cd)	IP Rating	IS Certificate	Colours	Options	Model
<b>Tactical Lights</b>															
2320	M6 2320	140	160	Xenon	2x CR123 Li	✓	82	1	145	5260	IPX4	-	B		2320
2330	M6 2330 Led Flashlight	140	160	LED	2x CR123 Li	✓	100	6	93	2184	IPX4	-	B		2330
2350	2350 LED Flashlight	107	100	LED	1 AA Alkaline	✓	100 (H) 10 (L)	1.45 (H) 15 (L)	141 (H) 44 (L)	5018 (H) 493 (L)	IPX7	-	B		2350
2360	2360 LED Flashlight	157	150	LED	2 AA Alkaline	✓	250 (H) 24 (L)	2.15 (H) 19 (L)	151 (H) 45 (L)	5692 (H) 512 (L)	IPX7	-	B		2360
2370	2370 Led Flashlight	163	180	LED	2 AA Alkaline	✓	106 (H) 13 (L)	3.45 (H) 41.15 (L)	158 (H) 52 (L)	6283 (H) 684 (L)	IPX4	-	B		2370
2380/R	2380R Rechargeable Flashlight	165	190	LED	1 3.7v, 2600mAh	✓	305 (H) 30 (L)	3.30 (H) 25 (L)	159 (H) 50 (L)	6317 (H) 613 (L)	IPX7	-	B		2380/R
2390	M6 3W 2390 LED Flashlight	135	160	LED	2x CR123 Li	✓	177	2	155	6002	IPX4	-	B, OD G		2390
3320	PM6 3320	134	100	Xenon	2x CR123 Li	✓	81	2	131	4330	IPX4	-	B		3320
3330	PM6 3330 LED Flashlight	134	100	LED	2x CR123 Li	✓	90	4	88	1959	IPX4		B, T, Y		3330
3390	3390 Knife/Lite Combo	84, knife	100, knife	LED	2x CR123 Li	✓	81	2	131	4330			B		3390
7000	7000 LED Flashlight	135	160	LED	2x CR123 Li	✓	602 (H) 64 (L)	1.30 (H) 16 (L)	233 (H) 75 (L)	13604 (H) 1409 (L)	IPX7		B		7000
7060	7060 LED Flashlight	220	290	LED	1 3.7v, 2800mAh	✓	368 (H) 18 (L)	3 (H) 45 (L)	199 (H) 42 (L)	9953 (H) 473 (L)	IPX4		B		7060
<b>Intrinsically Safe Torches</b>															
1820	Pocket Sabre™ 1820	148	240	Xenon	2x C Alkaline	✓*	22	7	146	5466	IPX7	CI II III D2	B, Y, O		1820
1900	MityLite™ 1900	104	50	Xenon	2x AAA Alkaline	✓	11	2	45	517	IPX7	CI D1	B, Y, O, BI, W, G		1900
1930	L1™ 1930 LED	67	30	LED	4x LR 44 Alkaline	✓	12	4	17	70	IPX4	CI D1	B, Y		1930
1965	MityLite 1965 LED	139	50	LED	2x AAA Alkaline	✓	21	4	51	756	IPX4	CI II III D1	B, Y		1965
2000	SabreLite™ 2000	198	360	Xenon	3x C Alkaline	×	53	5	158	6234	IPX7	CI D2	B, Y, O		2000
2010	SabreLite™ 2010 LED	206	380	LED	3x C Alkaline	×	109	32	144	5189	IPX7	CI II III D1	B, Y	PL Shroud	2010
2130	Mini Flasher™ 2130 LED	44	10	LED	2x L1154 Alkaline	✓	5	130	-	-	IPX7	-	Y		2130
2220	VB3™ 2220 LED	89	30	LED	2x CR2032	✓	9	34	12	38	IPX4	CI D1	B, O, Y, BI, R		2220
2300	MityLite™ 2300	143	100	Xenon	2x AA Alkaline	✓	11	5	43	478	IPX4	CI D1	B, Y		2300

\* Batteries included in select packaging

IPX4 = Water Resistant

IPX7 = Water Proof (submerged to 1 meter for 30 min.)

IPX8 = Submersible (submerged to 100 meters for 4 hours)



### PROTECTIVE CASES

U3 / 15 May Holman Drive Bassendean WA

PH : +61 (0)8 6161 0295

EM : enquiry@protectivecases.com.au

Note : Dimensions derived from various sources E&OE.